

# SAFETY DATA SHEET



UNLEADED GASOLINE

## Section 1. Identification

<b>Product name</b>	: UNLEADED GASOLINE
<b>Product description</b>	: Hydrocarbons and Additives
<b>Other means of identification</b>	: EXTRA UNLEADED 91; PREMIUM 95 KC; PREMIUM PETROL; REGULAR PETROL; SUPREME 95; SUPREME+ 98; UNLEADED 91 KC

### Relevant identified uses of the substance or mixture and uses advised against

<b>Identified uses</b>	: Fuel
<b>Uses advised against</b>	: This product is not recommended for any industrial, professional or consumer use other than the Identified Uses above.
<b>Supplier</b>	: Mobil Oil New Zealand Limited c/o Russell McVeagh Vero Centre 48 Shortland Street Auckland 1140 New Zealand
<b>24 Hour Emergency Telephone</b>	: +64 9-801 0034/ 0800 425 459 (CHEMTREC)
<b>National Poison Information Center</b>	: +64 3 479 7227/ Freephone 0800 764 766
<b>Supplier General Contact</b>	: +64 4 568 0400
<b>SDS Internet Address</b>	: <a href="http://www.sds.exxonmobil.com">www.sds.exxonmobil.com</a>

## Section 2. Hazards identification

<b>HSNO Classification</b>	: FLAMMABLE LIQUIDS - Category 1 CARCINOGENICITY - Category 2 ASPIRATION HAZARD - Category 1 LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2
----------------------------	---

This material is classified as hazardous according to criteria in the Hazardous Substances (Hazard Classification) Notice 2020.

This material is classified as DANGEROUS GOODS according to criteria in New Zealand Standard 5433:2012 Transport of Dangerous Goods on Land.

### GHS label elements

<b>Signal word</b>	: Danger
<b>Hazard statements</b>	: H224 - Extremely flammable liquid and vapour. H304 - May be fatal if swallowed and enters airways. H351 - Suspected of causing cancer. H411 - Toxic to aquatic life with long lasting effects.

### Precautionary statements

<b>General</b>	: P101 - If medical advice is needed, have product container or label at hand. P102 - Keep out of reach of children. P103 - Read label before use. Take all reasonable steps to ensure that the substance does not cause any significant adverse effects to the environment beyond the application area. Do not apply directly into or onto water.
----------------	--

## Section 2. Hazards identification

### Prevention

- : P202 - Do not handle until all safety precautions have been read and understood.
- P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P233 - Keep container tightly closed.
- P240 - Ground and bond container and receiving equipment.
- P241 - Use explosion-proof electrical, ventilating or lighting equipment.
- P242 - Use non-sparking tools.
- P243 - Take action to prevent static discharges.
- P273 - Avoid release to the environment.
- P280 - Wear protective gloves: < 1 hour (breakthrough time): Nitrile, minimum 0.38 mm thickness or comparable protective barrier material. Wear protective clothing. Wear eye or face protection. Wear hearing protection.

### Response

- : P301 + P331, P310 - IF SWALLOWED: Do NOT induce vomiting. Immediately call a POISON CENTER or doctor.
- P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
- P308 + P313 - IF exposed or concerned: Get medical advice or attention.
- P370 + P378 - In case of fire: Use water fog, foam, dry chemical or carbon dioxide (CO<sub>2</sub>) to extinguish flames.
- P391 - Collect spillage.

### Storage

- : P403 + P235 - Store in a well-ventilated place. Keep cool.
- P405 - Store locked up.

### Disposal

- : P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.

### Symbol

- :
 



### Contains

- : unleaded gasoline

### Other hazards which do not result in classification

- : None known.

### Nota

- : This material should not be used for any other purpose than the intended use in Section 1 without expert advice. Health studies have shown that chemical exposure may cause potential human health risks which may vary from person to person.

## Section 3. Composition/information on ingredients

### Substance/mixture

- : Substance

### Chemical name

- : unleaded gasoline

Ingredient name	% (w/w)	Identifiers
gasoline	>99	CAS: 86290-81-5
ethylbenzene	≤15	CAS: 100-41-4
cumene	≤15	CAS: 98-82-8
xylene	≥5 - ≤10	CAS: 1330-20-7
benzene	≥1 - ≤5	CAS: 71-43-2

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

## Section 4. First-aid measures

### Description of necessary first aid measures

**Eye contact** : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.

**Inhalation** : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

**Skin contact** : Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. If product is injected into or under the skin, or into any part of the body, regardless of the appearance of the wound or its size, the individual should be evaluated immediately by a physician as a surgical emergency. Even though initial symptoms from high pressure injection may be minimal or absent, early surgical treatment within the first few hours may significantly reduce the ultimate extent of injury. Wash clothing before reuse. Clean shoes thoroughly before reuse. Continue to rinse for at least 10 minutes. Get medical attention.

**Ingestion** : Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Aspiration hazard if swallowed. Can enter lungs and cause damage. Do not induce vomiting. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

### Most important symptoms/effects, acute and delayed

#### Potential acute health effects

**Eye contact** : No known significant effects or critical hazards.

**Inhalation** : No known significant effects or critical hazards.

**Skin contact** : Causes mild skin irritation.

**Ingestion** : May be fatal if swallowed and enters airways.

#### Over-exposure signs/symptoms

**Eye contact** : Adverse symptoms may include the following:  
pain or irritation  
watering  
redness

**Inhalation** : Numbness, muscle cramps, weakness and paralysis that may be delayed.

**Skin contact** : Adverse symptoms may include the following:  
irritation  
redness  
Local necrosis as evidenced by delayed onset of pain and tissue damage a few hours after injection.

**Ingestion** : Adverse symptoms may include the following:  
nausea or vomiting

### Indication of immediate medical attention and special treatment needed, if necessary

**Notes to physician** : If ingested, material may be aspirated into the lungs and cause chemical pneumonitis. Treat appropriately. This material, or a component, may be associated with cardiac sensitization following very high exposures (well above occupational exposure limits) or with concurrent exposure to high stress levels or heart-stimulating substances like epinephrine. Administration of such substances should be avoided.

**Specific treatments** : No specific treatment.

## Section 4. First-aid measures

**Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

See toxicological information (Section 11)

## Section 5. Firefighting measures

### Extinguishing media

**Suitable extinguishing media** : Use dry chemical, CO<sub>2</sub>, water spray (fog) or foam.

**Unsuitable extinguishing media** : Do not use water jet.

**Specific hazards arising from the chemical** : Extremely flammable liquid and vapour. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. This material is toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

**Hazardous combustion products** : Aldehydes, Incomplete combustion products, Oxides of carbon, Smoke, Fume, sulfur oxides

**Special protective actions for fire-fighters** : Use standard firefighting procedures and consider the hazards of other involved materials. Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool. Assure an extended cooling down period to prevent re-ignition. Prevent run-off from fire control or dilution from entering streams, sewers or drinking water supply. No action shall be taken involving any personal risk or without suitable training.

**Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

## Section 6. Accidental release measures

### NOTIFICATION PROCEDURES

In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations.

### Personal precautions, protective equipment and emergency procedures

**For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Put on appropriate personal protective equipment. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate.

**For emergency responders** : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

**Environmental precautions** : Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.

### Methods and material for containment and cleaning up

## Section 6. Accidental release measures

### Small spill

- Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

### Large spill

- Stop leak if without risk. Eliminate all ignition sources. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product. Do not confine in area of spill. Allow liquid to evaporate from the surface. Seek the advice of a specialist before using dispersants. Advise occupants and shipping in downwind areas of fire and explosion hazard and warn them to stay clear. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Water spill and land spill recommendations are based on the most likely spill scenario for this material; however, geographic conditions, wind, temperature, (and in the case of a water spill) wave and current direction and speed may greatly influence the appropriate action to be taken. For this reason, local experts should be consulted. Note: Local regulations may prescribe or limit action to be taken.

## Section 7. Handling and storage

### Precautions for safe handling

#### Protective measures

- Put on appropriate personal protective equipment (see Section 8). Avoid exposure - obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not swallow. Avoid breathing vapour or mist. Avoid release to the environment. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. To avoid fire or explosion, dissipate static electricity during transfer by earthing and bonding containers and equipment before transferring material. Empty containers retain product residue and can be hazardous. Do not reuse container. It is dangerous and/or unlawful to put petrol into unapproved containers. Do not fill container while it is in or on a vehicle. Static electricity may ignite vapour and cause fire. Place container on ground when filling and keep nozzle in contact with container. Do not use electronic devices (including but not limited to cellular phones, computers, calculators, pagers or other electronic devices, etc.) during safety critical tasks, such as bulk fuel loading or unloading operations, or in storage areas where vapours may be present, unless the devices are certified intrinsically safe by an approved national testing agency and to the safety standards required by national and/or local laws and regulations. For use as a motor fuel only. Do not siphon by mouth.

#### Advice on general occupational hygiene

- Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

#### Static Accumulator

- This material is a static accumulator. A liquid is typically considered a nonconductive, static accumulator if its conductivity is below 100 pS/m (100x10E-12 Siemens per meter) and is considered a semiconductive, static accumulator if its conductivity is below 10,000 pS/m. Whether a liquid is nonconductive or semiconductive, the precautions are the same. A number of factors, for example liquid temperature, presence of contaminants, anti-static additives and filtration can greatly influence the conductivity of a liquid.

## Section 7. Handling and storage

**Conditions for safe storage, including any incompatibilities** : Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidising materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

## Section 8. Exposure controls/personal protection

### Control parameters

#### Occupational exposure limits

Ingredient name	Exposure limits
unleaded gasoline	<b>ExxonMobil (COMPANY)</b> TWA 8 hours: 100 ppm. Form: Vapour.. TWA 8 hours: 300 mg/m <sup>3</sup> . Form: Vapour..
gasoline	<b>ACGIH TLV (United States, 1/2025)</b> TWA 8 hours: 300 ppm. TWA 8 hours: 890 mg/m <sup>3</sup> . STEL 15 minutes: 500 ppm. STEL 15 minutes: 1480 mg/m <sup>3</sup> . <b>ExxonMobil (COMPANY)</b> STEL 15 minutes: 200 ppm. TWA 8 hours: 100 ppm.
ethylbenzene	<b>HSWA 2015 - HSW (GRWM) 2016. Workplace exposure standards (WES) (New Zealand, 2/2025)</b> Absorbed through skin , Ototoxicant. WES-TWA 8 hours: 20 ppm. WES-TWA 8 hours: 88 mg/m <sup>3</sup> . WES-STEL 15 minutes: 176 mg/m <sup>3</sup> . WES-STEL 15 minutes: 40 ppm. <b>ACGIH TLV (United States, 1/2025)</b> Ototoxicant. TWA 8 hours: 20 ppm.
cumene	<b>HSWA 2015 - HSW (GRWM) 2016. Workplace exposure standards (WES) (New Zealand, 2/2025)</b> Absorbed through skin. WES-TWA 8 hours: 10 ppm. WES-TWA 8 hours: 50 mg/m <sup>3</sup> . WES-STEL 15 minutes: 50 ppm. WES-STEL 15 minutes: 250 mg/m <sup>3</sup> . <b>ACGIH TLV (United States, 1/2025)</b> TWA 8 hours: 5 ppm. <b>ExxonMobil (COMPANY)</b> Absorbed through skin. TWA 8 hours: 5 ppm.
xylene	<b>HSWA 2015 - HSW (GRWM) 2016. Workplace exposure standards (WES) (New Zealand, 2/2025) [xylene (o-, m-, p-isomers)]</b> Ototoxicant. WES-TWA 8 hours: 50 ppm. WES-TWA 8 hours: 217 mg/m <sup>3</sup> . <b>ACGIH TLV (United States, 1/2025) [p-xylene and mixtures containing p-xylene]</b> Ototoxicant. TWA 8 hours: 20 ppm.
isopentane	<b>ACGIH TLV (United States, 1/2025) [Pentane]</b> TWA 8 hours: 1000 ppm.
1,2,4-trimethylbenzene	<b>HSWA 2015 - HSW (GRWM) 2016. Workplace exposure standards (WES) (New Zealand, 2/2025) [Trimethyl benzene]</b>

## Section 8. Exposure controls/personal protection

	WES-TWA 8 hours: 25 ppm. WES-TWA 8 hours: 123 mg/m <sup>3</sup> . <b>ACGIH TLV (United States, 1/2025)</b> TWA 8 hours: 10 ppm.
toluene	<b>HSWA 2015 - HSW (GRWM) 2016. Workplace exposure standards (WES) (New Zealand, 2/2025)</b> Absorbed through skin , Ototoxicant. WES-TWA 8 hours: 20 ppm. WES-TWA 8 hours: 75 mg/m <sup>3</sup> . WES-STEL 15 minutes: 377 mg/m <sup>3</sup> . WES-STEL 15 minutes: 100 ppm. <b>ACGIH TLV (United States, 1/2025)</b> Ototoxicant. TWA 8 hours: 20 ppm.
pentane	<b>HSWA 2015 - HSW (GRWM) 2016. Workplace exposure standards (WES) (New Zealand, 2/2025)</b> WES-TWA 8 hours: 600 ppm. WES-TWA 8 hours: 1770 mg/m <sup>3</sup> . WES-STEL 15 minutes: 2210 mg/m <sup>3</sup> . WES-STEL 15 minutes: 750 ppm. <b>ACGIH TLV (United States, 1/2025) [Pentane]</b> TWA 8 hours: 1000 ppm.
hexane (containing < 5 % n-hexane (203-777-6))	<b>HSWA 2015 - HSW (GRWM) 2016. Workplace exposure standards (WES) (New Zealand, 2/2025) [Hexane, Other isomers]</b> WES-TWA 8 hours: 500 ppm. WES-TWA 8 hours: 1760 mg/m <sup>3</sup> . WES-STEL 15 minutes: 3500 mg/m <sup>3</sup> . WES-STEL 15 minutes: 1000 ppm. <b>ACGIH TLV (United States, 1/2025) [branched hexane isomers]</b> TWA 8 hours: 200 ppm. <b>ACGIH TLV (United States, 1/2025) [hexane]</b> Absorbed through skin. TWA 8 hours: 100 ppm. <b>HSWA 2015 - HSW (GRWM) 2016. Workplace exposure standards (WES) (New Zealand, 2/2025)</b>
butane	WES-TWA 8 hours: 800 ppm. WES-TWA 8 hours: 1900 mg/m <sup>3</sup> . <b>ACGIH TLV (United States, 1/2025) [Butane]</b> Explosive potential. STEL 15 minutes: 1000 ppm. <b>HSWA 2015 - HSW (GRWM) 2016. Workplace exposure standards (WES) (New Zealand, 2/2025) [Trimethyl benzene]</b> WES-TWA 8 hours: 25 ppm. WES-TWA 8 hours: 123 mg/m <sup>3</sup> . <b>ACGIH TLV (United States, 1/2025) [trimethyl benzene, isomers]</b> TWA 8 hours: 10 ppm. <b>HSWA 2015 - HSW (GRWM) 2016. Workplace exposure standards (WES) (New Zealand, 2/2025) [Hexane, Other isomers]</b> WES-TWA 8 hours: 500 ppm. WES-TWA 8 hours: 1760 mg/m <sup>3</sup> . WES-STEL 15 minutes: 3500 mg/m <sup>3</sup> . WES-STEL 15 minutes: 1000 ppm. <b>ACGIH TLV (United States, 1/2025) [branched hexane isomers]</b> TWA 8 hours: 200 ppm. <b>ACGIH TLV (United States, 1/2025) [hexane]</b> Absorbed through skin. TWA 8 hours: 100 ppm. <b>HSWA 2015 - HSW (GRWM) 2016. Workplace exposure standards (WES) (New Zealand, 2/2025) [Hexane, Other isomers]</b> WES-TWA 8 hours: 500 ppm. WES-TWA 8 hours: 1760 mg/m <sup>3</sup> . WES-STEL 15 minutes: 3500 mg/m <sup>3</sup> . WES-STEL 15 minutes: 1000 ppm.
2,3-dimethylbutane	<b>HSWA 2015 - HSW (GRWM) 2016. Workplace exposure standards (WES) (New Zealand, 2/2025) [Hexane, Other isomers]</b> WES-TWA 8 hours: 500 ppm. WES-TWA 8 hours: 1760 mg/m <sup>3</sup> . WES-STEL 15 minutes: 3500 mg/m <sup>3</sup> . WES-STEL 15 minutes: 1000 ppm. <b>ACGIH TLV (United States, 1/2025) [hexane]</b> Absorbed through skin. TWA 8 hours: 100 ppm. <b>HSWA 2015 - HSW (GRWM) 2016. Workplace exposure standards (WES) (New Zealand, 2/2025) [Hexane, Other isomers]</b> WES-TWA 8 hours: 500 ppm. WES-TWA 8 hours: 1760 mg/m <sup>3</sup> . WES-STEL 15 minutes: 3500 mg/m <sup>3</sup> .

## Section 8. Exposure controls/personal protection

benzene	<p>WES-STEL 15 minutes: 1000 ppm.  <b>ACGIH TLV (United States, 1/2025) [branched hexane isomers]</b>  TWA 8 hours: 200 ppm.</p> <p><b>ACGIH TLV (United States, 1/2025) [hexane]</b> Absorbed through skin.  TWA 8 hours: 100 ppm.</p> <p><b>HSWA 2015 - HSW (GRWM) 2016. Workplace exposure standards (WES) (New Zealand, 2/2025)</b> Absorbed through skin.  WES-TWA 8 hours: 0.05 ppm.  WES-TWA 8 hours: 0.16 mg/m<sup>3</sup>.</p> <p><b>ACGIH TLV (United States, 1/2025)</b> Absorbed through skin.  TWA 8 hours: 0.02 ppm.</p> <p><b>ExxonMobil (COMPANY)</b> Absorbed through skin.  STEL 15 minutes: 1 ppm.  TWA 8 hours: 0.2 ppm.</p>
3-methylhexane	<p><b>ACGIH TLV (United States, 1/2025) [heptane]</b> Ototoxicant.  TWA 8 hours: 200 ppm.  STEL 15 minutes: 400 ppm.</p>
n-hexane	<p><b>HSWA 2015 - HSW (GRWM) 2016. Workplace exposure standards (WES) (New Zealand, 2/2025)</b> Ototoxicant.  WES-TWA 8 hours: 20 ppm.  WES-TWA 8 hours: 72 mg/m<sup>3</sup>.</p> <p><b>ACGIH TLV (United States, 1/2025)</b> Absorbed through skin.  TWA 8 hours: 50 ppm.</p>

NOTE: Limits/standards shown for guidance only. Follow applicable regulations.

### Biological exposure indices

Ingredient name	Exposure indices
ethylbenzene	<p><b>HSWA 2015 - HSW (GRWM) 2016. Biological exposure indices (BEI) (New Zealand, 2/2025)</b>  BEI: 0.25 g/g creatinine, sum of mandelic acid and phenylglyoxylic acids [in urine]. Sampling time: end of shift or end of exposure.</p>
xylene	<p><b>HSWA 2015 - HSW (GRWM) 2016. Biological exposure indices (BEI) (New Zealand, 2/2025) [xylene]</b>  BEI: 1.5 g/l, methylhippuric acid [in urine]. Sampling time: end of shift.</p>
benzene	<p><b>HSWA 2015 - HSW (GRWM) 2016. Biological exposure indices (BEI) (New Zealand, 2/2025)</b>  BEI: 2 µg/g creatinine, S-phenylmercapturic acid [in urine]. Sampling time: end of shift.</p>

**Appropriate engineering controls** : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapour or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

**Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

### Individual protection measures

## Section 8. Exposure controls/personal protection

<b>Hygiene measures</b>	: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
<b>Eye/face protection</b>	: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.
<b>Skin protection</b>	
<b>Hand protection</b>	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. < 1 hour (breakthrough time): Nitrile, minimum 0.38 mm thickness or comparable protective barrier material
<b>Body protection</b>	: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.
<b>Other skin protection</b>	: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
<b>Respiratory protection</b>	: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use. Recommended: organic vapour filter (Type A)

## Section 9. Physical and chemical properties and safety characteristics

**Note: Physical and chemical properties are provided for safety, health and environmental considerations only and may not fully represent product specifications. Contact the Supplier for additional information.**

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

### Appearance

<b>Physical state</b>	: Liquid.
<b>Colour</b>	: Clear (May Be Dyed)
<b>Odour</b>	: Petroleum/Solvent
<b>Odour threshold</b>	: Not available.
<b>pH</b>	: Not applicable.
<b>Melting point/freezing point</b>	: Not available.
<b>Boiling point or initial boiling point and boiling range</b>	: >20°C (>68°F)
<b>Flash point</b>	: Closed cup: <-40°C (<-40°F) [ASTM D-56]
<b>Evaporation rate</b>	: >10 (butyl acetate = 1)
<b>Flammability</b>	: Flammable liquids - Category 1
<b>Lower and upper explosion limit/flammability limit</b>	: Lower: 1.2% Upper: 8.2%
<b>Vapour pressure</b>	: 517.54 mm Hg [34 °C]

## Section 9. Physical and chemical properties and safety characteristics

<b>Relative vapour density</b>	: Not available.
<b>Relative density</b>	: 0.72 to 0.78
<b>Solubility in water</b>	: Negligible
<b>Partition coefficient: n-octanol/water</b>	: >3
<b>Auto-ignition temperature</b>	: >250°C (>482°F)
<b>Decomposition temperature</b>	: Not available.
<b>Viscosity</b>	: <1 cSt [40 °C]
<b>Particle characteristics</b>	
<b>Median particle size</b>	: Not applicable.

## Section 10. Stability and reactivity

<b>Reactivity</b>	: No specific test data related to reactivity available for this product or its ingredients.
<b>Chemical stability</b>	: The product is stable.
<b>Possibility of hazardous reactions</b>	: Under normal conditions of storage and use, hazardous reactions will not occur.
<b>Conditions to avoid</b>	: Avoid all possible sources of ignition (spark or flame). Do not pressurise, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition.
<b>Incompatible materials</b>	: Reactive or incompatible with the following materials:,oxidising materials,Strong oxidisers, Halogens, strong acids, Alkalies
<b>Hazardous decomposition products</b>	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## Section 11. Toxicological information

### Information on toxicological effects

#### Acute toxicity

Product/ingredient name	Result
Unleaded gasoline	<b>Rabbit - Dermal - LD50</b> >2000 mg/kg <b>Rat - Oral - LD50</b> >5000 mg/kg <b>Rat - Inhalation - LC50 Vapour</b> >5000 mg/m <sup>3</sup> [4 hours] <b>Rat - Oral - LD50</b> 3.5 g/kg <b>Rat - Inhalation - LC50 Vapour</b> 17.8 mg/l [4 hours]
ethylbenzene	

#### Conclusion/Summary

<b>Inhalation</b>	: Minimally Toxic. Data available. Based on test data for structurally similar materials. Test(s) equivalent or similar to OECD Guideline 403
<b>Dermal</b>	: Minimally Toxic. Data available. Based on test data for structurally similar materials. Test(s) equivalent or similar to OECD Guideline 402
<b>Oral</b>	: Minimally Toxic. Data available. Based on test data for structurally similar materials. Test(s) equivalent or similar to OECD Guideline 401

#### Irritation/Corrosion

#### Conclusion/Summary

<b>Version</b> : 4	<b>Date of issue/Date of revision</b> : 26 December 2025
--------------------	--

## Section 11. Toxicological information

**Skin** : Mildly irritating to skin with prolonged exposure. Data available. Based on test data for structurally similar materials. Test(s) equivalent or similar to OECD Guideline 404

**Eyes** : May cause mild, short-lasting discomfort to eyes. Data available. Based on test data for structurally similar materials. Test(s) equivalent or similar to OECD Guideline 405

**Respiratory** : Negligible hazard at ambient/normal handling temperatures. No end point data for material. Elevated temperatures or mechanical action may form vapours, mist, or fumes which may be irritating to the eyes, nose, throat, or lungs.

### Sensitisation

#### **Conclusion/Summary**

**Skin** : Not expected to be a skin sensitizer. Data available. Based on test data for structurally similar materials. Test(s) equivalent or similar to OECD Guideline 406

**Respiratory** : Not expected to be a respiratory sensitizer. No end point data for material. Based on test data for structurally similar materials.

### Mutagenicity

#### **Conclusion/Summary**

: Not expected to be a germ cell mutagen. Data available. Based on test data for structurally similar materials. Test(s) equivalent or similar to OECD Guideline 471 475 476

### Carcinogenicity

#### **Conclusion/Summary**

: May cause cancer. Data available. Based on test data for structurally similar materials. Test(s) equivalent or similar to OECD Guideline 451

### Classification

Product/ingredient name	IARC
gasoline	2B
ethylbenzene	2B
cumene	2B
xylene	3
benzene	1

**Gasoline – IARC 2B:** In March 2025, IARC announced that a forthcoming Monograph (expected to be published in 2026) will revise its classification of gasoline to Group 1 (carcinogenic to humans). IARC's announcement in *The Lancet Oncology* was not accompanied by the full range of scientific literature relied upon for each disease endpoint (acute myelogenous leukemia & bladder cancer). Until the Monograph is published and the data relied upon is made available, ExxonMobil will be unable to evaluate whether IARC's classification accurately reflects the scientific evidence used in making the classification, which is contrary to and inconsistent with the weight of known scientific literature.

### Reproductive toxicity

#### **Conclusion/Summary**

: Not expected to be a reproductive toxicant. Data available. Based on test data for structurally similar materials. Test(s) equivalent or similar to OECD Guideline 416 421

### Specific target organ toxicity (single exposure)

#### **Conclusion/Summary**

: Not expected to cause organ damage from a single exposure. No end point data for material.

### Specific target organ toxicity (repeated exposure)

Product/ingredient name	Category	Target organs
unleaded gasoline	Not applicable.	-

#### **Conclusion/Summary**

: Not expected to cause organ damage from prolonged or repeated exposure. Data available. Based on test data for structurally similar materials. Test(s) equivalent or similar to OECD Guideline 410 412 453

### Aspiration hazard

Product/ingredient name	Result
unleaded gasoline	Category 1

#### **Conclusion/Summary**

: May be fatal if swallowed and enters airways. Based on physico-chemical properties of the material. Data available. Based on physico-chemical properties of the material.

## Section 11. Toxicological information

### Other information

#### Contains

: TRIMETHYLBENZENE: Long-term inhalation exposure of trimethylbenzene caused effects to the blood in laboratory animals. ETHYLBENZENE: Caused cancer in laboratory animal studies. The relevance of these findings to humans is uncertain. BENZENE: Caused cancer (acute myeloid leukemia and myelodysplastic syndrome), damage to the blood-producing system, and serious blood disorders in human studies. Caused genetic effects and effects on the immune system in laboratory animal and some human studies. Caused toxicity to the fetus and cancer in laboratory animal studies. CUMENE: Repeated inhalation exposure of cumene vapour produced damage in the kidney of male rats only. These effects are believed to be species specific and are not relevant to humans. N-HEXANE: Prolonged and/or repeated exposures to n-Hexane can cause progressive and potentially irreversible damage to the peripheral nervous system (e.g. fingers, feet, arms, legs, etc.). Simultaneous exposure to Methyl Ethyl Ketone (MEK) or Methyl Isobutyl Ketone (MIBK) and n-Hexane can potentiate the risk of adverse effects from n-Hexane on the peripheral nervous system. n-Hexane has been shown to cause testicular damage at high doses in male rats. The relevance of this effect for humans is unknown. TOLUENE : Concentrated, prolonged or deliberate inhalation may cause brain and nervous system damage. Prolonged and repeated exposure of pregnant animals (> 1500 ppm) have been reported to cause adverse fetal developmental effects.

#### Product

: Gasoline unleaded: Carcinogenic in animal tests. Chronic inhalation studies resulted in liver tumours in female mice and kidney tumours in male rats. Neither result considered significant for human health risk assessment by the United States EPA and others. Did not cause mutations in-vitro or in-vivo. Negative in inhalation developmental studies and reproductive tox studies. Inhalation of high concentrations in animals resulted in reversible central nervous system depression, but no persistent toxic effect on the nervous system. Non-sensitizing in test animals. Caused nerve damage in humans from abusive use (sniffing). Laboratory animal studies have shown that prolonged and repeated inhalation exposure to light hydrocarbon vapours in the same boiling range as this product can produce adverse kidney effects in male rats. However, these effects were not observed in similar studies with female rats, male and female mice, or in limited studies with other animal species. Additionally, in a number of human studies, there was no clinical evidence of such effects at normal occupational levels. In 1991, The U.S. EPA determined that the male rat kidney is not useful for assessing human risk. Vapour concentrations above recommended exposure levels are irritating to the eyes and the respiratory tract, may cause headaches and dizziness, are anaesthetic and may have other central nervous system effects. Gasoline unleaded: Carcinogenic in animal tests. Chronic inhalation studies resulted in liver tumours in female mice and kidney tumours in male rats. Neither result considered significant for human health risk assessment by the United States EPA and others. Did not cause mutations in-vitro or in-vivo. Negative in inhalation developmental studies and reproductive tox studies. Inhalation of high concentrations in animals resulted in reversible central nervous system depression, but no persistent toxic effect on the nervous system. Non-sensitizing in test animals. Caused nerve damage in humans from abusive use (sniffing). Exposure to this material, or one of its components, in situations where there is the potential for high levels, such as in confined spaces or with abuse, may result in abnormal heart rhythm (arrhythmia). High-level exposure to hydrocarbons (above occupational exposure limits) may initiate arrhythmia in a worker that is undergoing stress or is taking a heart-stimulating substance such as epinephrine, a nasal decongestant, or an asthma or cardiovascular drug. Small amounts of liquid aspirated into the lungs during ingestion or from vomiting may cause chemical pneumonitis or pulmonary edema.

## Section 12. Ecological information

The information given is based on data for the material, components of the material, or for similar materials, through the application of bridging principals.

### Aquatic and terrestrial toxicity

Product/ingredient name	Result
Unleaded gasoline	<p><b>Acute - EL50</b> daphnia - <i>Daphnia magna</i> 1 to 100 mg/l - data for similar materials [48 hours]</p> <p><b>Acute - EL50</b> Algae - <i>Pseudokirchneriella subcapitata</i> 1 to 1000 mg/l - data for similar materials [72 hours]</p> <p><b>Acute - LL50</b> Fish - <i>Fish</i> 1 to 100 mg/l - data for similar materials [96 hours]</p> <p><b>Chronic - NOEL</b> Algae - <i>Pseudokirchneriella subcapitata</i> 1 to 100 mg/l - data for similar materials [72 hours]</p> <p><b>Chronic - NOEL</b> daphnia - <i>Daphnia magna</i> 1 to 10 mg/l - data for similar materials [21 days]</p>

### Conclusion/Summary

**Acute toxicity** : Toxic to aquatic life.

**Chronic toxicity** : Toxic to aquatic life with long lasting effects.

### Persistence and degradability

Product/ingredient name	Result
Unleaded gasoline	Ready Biodegradability <60% [28 days]

**Biodegradability** : Majority of components -- Expected to be inherently biodegradable

**Atmospheric Oxidation** : More volatile component -- Expected to degrade rapidly in air

### Bioaccumulative potential

**Conclusion/Summary** : Majority of components -- Has the potential to bioaccumulate, however metabolism or physical properties may reduce the bioconcentration or limit bioavailability.

### Mobility in soil

**Mobility** : Less volatile component -- Expected to partition to sediment and wastewater solids. Low solubility and floats and is expected to migrate from water to the land. More volatile component -- Highly volatile, will partition rapidly to air. Not expected to partition to sediment and wastewater solids.

### Other ecological information

**Other adverse effects** : No known significant effects or critical hazards.

## Section 13. Disposal considerations

**Disposal methods** : The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

## Section 13. Disposal considerations

Empty Container Warning (where applicable): Empty containers may contain residue and can be dangerous. Do not attempt to refill or clean containers without proper instructions. Empty drums should be completely drained and safely stored until appropriately reconditioned or disposed. Empty containers should be taken for recycling, recovery, or disposal through suitably qualified or licensed contractor and in accordance with governmental regulations. DO NOT PRESSURISE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND, OR EXPOSE SUCH CONTAINERS TO HEAT, FLAME, SPARKS, STATIC ELECTRICITY, OR OTHER SOURCES OF IGNITION. THEY MAY EXPLODE AND CAUSE INJURY OR DEATH.

## Section 14. Transport information

	New Zealand	IMDG	IATA
<b>UN number</b>	UN1203	UN1203	UN1203
<b>UN proper shipping name</b>	GASOLINE	GASOLINE	Gasoline
<b>Transport hazard class(es)</b>	3	3	3
<b>Label(s) / Mark(s)</b>	 	 	
<b>Packing group</b>	II	II	II
<b>Environmental hazards</b>	Yes.	Yes.	Yes. The environmentally hazardous substance mark is not required.

### Additional information

**New Zealand** : The marine pollutant mark is not required when transported by rail.  
Hazchem code 3YE  
Special provisions 243, 363

**IMDG** : The marine pollutant mark is not required when transported in sizes of  $\leq$  5 L or  $\leq$  5 kg.  
Emergency schedules F-E, S-E  
Special provisions 243  
Flash point  $<-40$  °C C.C.

**IATA** : The environmentally hazardous substance mark may appear if required by other transportation regulations.  
Quantity limitation Passenger and Cargo Aircraft: 5 L. Packaging instructions: 353. Cargo Aircraft Only: 60 L. Packaging instructions: 364. Limited Quantities - Passenger Aircraft: 1 L. Packaging instructions: Y341.  
Special provisions A100

**Special precautions for user** : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

**Transport in bulk according to IMO instruments** : Not applicable.

## Section 15. Regulatory information

<b>HSNO Approval Number</b>	:	HRC000003
<b>HSNO Group Standard</b>	:	Not available.
<b>HSNO Classification</b>	:	FLAMMABLE LIQUIDS - Category 1 CARCINOGENICITY - Category 2 ASPIRATION HAZARD - Category 1 LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2

### Inventory list

<b>Australia inventory (AIIC)</b>	:	All components are listed or exempted.
<b>Canada inventory (DSL-NDSL)</b>	:	All components are listed or exempted.
<b>China inventory (IECSC)</b>	:	Not determined.
<b>Japan inventory (CSCL)</b>	:	All components are listed or exempted.
<b>Japan inventory (Industrial Safety and Health Act)</b>	:	Not determined.
<b>New Zealand Inventory of Chemicals (NZIoC)</b>	:	All components are listed or exempted.
<b>Philippines inventory (PICCS)</b>	:	All components are listed or exempted.
<b>Korea inventory (KECI)</b>	:	All components are listed or exempted.
<b>Taiwan Chemical Substances Inventory (TCSI)</b>	:	All components are listed or exempted.
<b>United States inventory (TSCA 8b)</b>	:	All components are active or exempted.

## Section 16. Other information

### History

<b>Date of issue/Date of revision</b>	:	26 December 2025
<b>Date of previous issue</b>	:	27 February 2024
<b>Version</b>	:	4
<b>Key to abbreviations</b>	:	ADG = Australian Dangerous Goods ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association IBC = Intermediate Bulk Container IMDG = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail SGG = Segregation Group UN = United Nations
<b>References</b>	:	Not available.

 Indicates information that has changed from previously issued version.

**Product code** : 1163560

[Notice to reader](#)

## Section 16. Other information

"The information and recommendations contained herein are, to the best of ExxonMobil's knowledge and belief, accurate and reliable as of the date issued. You can contact ExxonMobil to insure that this document is the most current available from ExxonMobil. The information and recommendations are offered for the user's consideration and examination. It is the user's responsibility to satisfy itself that the product is suitable for the intended use. If buyer repackages this product, it is the user's responsibility to insure proper health, safety and other necessary information is included with and/or on the container. Appropriate warnings and safe-handling procedures should be provided to handlers and users. Alteration of this document is strictly prohibited. Except to the extent required by law, re-publication or retransmission of this document, in whole or in part, is not permitted. The term, ""ExxonMobil"" is used for convenience, and may include any one or more of ExxonMobil Chemical Company, Exxon Mobil Corporation, or any affiliates in which they directly or indirectly hold any interest."